

Power

AlphaCell™ 85 GXL HP

Valve Regulated Lead Acid Batteries



- Designed specifically for standby applications
- Deliver 100% “out-of-box” capacity — no cycling required
- Premium Gel model offers 50% longer life than traditional gel batteries
- Full replacement, non-prorated warranties
- Silver Alloy minimizes grid corrosion
- Maintenance-free threaded inserts; no periodic retorquing

Alpha's standby battery offering incorporates true Gel Cell and Silver Alloy grid battery technologies, ensuring optimal performance for your outdoor cable, traffic or WiFi application. AlphaCell batteries provide the ultimate warranty, longest runtimes and superior longevity in today's demanding outdoor non-temperature controlled cable power environments.



AlphaCell 85 GXL HP

General Specifications

Warranty ¹ :	5 year Full replacement
Service Life:	Extended
Runtime (minutes) ² :	85
Sealed VRLA:	Valve regulated lead acid
Heat Resistant:	Extreme
Hydrogen Emission:	Low
Terminals:	Threaded Insert 10-32 UNF

Specifications

Silver Alloy:	Yes
Typical Runtime (minutes) ² :	85
Cells Per Unit:	6
Voltage Per Unit:	12.8
Conductance Value:	600
Max. Discharge Current (A):	600
Short Circuit Current (A):	2200
10sec Volts @ 100A:	10.8
Ohms Impedance 60Hz:	0.0065
Capacity at 20hrs: (to 1.75VPC)	50Ah
BCI Group Size:	22
Weight (lb/kg):	39.6/18
Height w/ Terminals (in/mm):	8.09/205.6
Width (in/mm) ³ :	8.99/228.3
Depth (in/mm) ³ :	5.47/138.9
Operating Temperature Range	
Discharge (°C):	-40 to 71°C
Charge (with temp compensation):	-23 to 60°C
Float Charging Voltage (Vdc):	13.5 to 13.8
AC Ripple Charger:	0.5% RMS or 1.5% of float charge voltage recommended for best results. Maximum allowed = 4% P-P

Notes:

- ¹ Warranty varies by country and region. Consult your sales person for details.
- ² Runtimes calculated using a 25A DC constant current load with voltage discharge to 1.75V/cell @ 25°C.
- ³ Dimensions at top of battery.

Current Discharge Ratings Table in Amps (end Voltage 1.75VPC)

Hours	1	2	3	4	6	8	10	12	20	24	48	72	100
85 GXL HP	33.2	18.8	13.3	10.4	7.34	5.70	4.68	3.97	2.50	2.12	1.11	0.76	0.56

Distributed by: www.tacel.ca info@tacel.ca		Head Office 179 Bartley Dr. Unit B Toronto, ON M4A 1E6	Phone 416 750-4646 Toll Free 877 750-4646 Fax 416 750-4649
--	---	---	--

For contact information visit www.alpha.com

The Alpha Group >	North America	Europe, Middle East & Africa	Asia Pacific	Latin & South America	
	USA Tel: +1 360 647 2360 Fax: +1 360 671 4936 Canada Tel: +1 604 430 1476 Fax: +1 604 430 8908	Cyprus Tel: +357 25 375 675 Fax: +357 52 359 595 Russia Tel: +7 495 925 9844 Fax: +7 495 916 1349	Germany Tel: +49 9122 79889 0 Fax: +49 9122 79889 21 United Kingdom Tel: +44 1279 501110 Fax: +44 1279 659870	Lithuania Tel: +370 5 210 5291 Fax: +370 5 210 5292 P.R. China Tel: +852 2736 8663 Fax: +852 2199 7988	Contact USA office