

PRODUCT DATA SHEET

WC142CN 14 AWG 2 COND PVC POLYOLEFIN INSULATION FOIL SHIELD CSA style - AWM, CMGUL style - CMFlame Test - FT4

Product Number: WC142CN

Description: 14 AWG (41 X 30) TC 2 COND., POLYOLEFIN INSULATION, O/A ALUM/POLY SHIELD, STC DRAIN, GRAY PVC JACKET

Image file:



Image shown is a representation and does not necessarily reflect the actual product

AWG: 14

Stranding: 41 X 30

Conductor: TC

Insulation: 0.51mm PO

Number Conductors: 2

Capacitance: 98 pF/m (conductor to conductor)
190 pF/m (1 cond. and other conductors connected to shield)

First Shield: O/A ALUM/POLY

First Drain: STC

Jacket Type: GRAY PVC

Nom. Cable OD: 7.67mm

Voltage: 600

Temperature: 0°C to +80°C

Weight: 83 kgs/km

CSA: AWM, CMG

UL: CM

Flame Test: FT4

Table 7

Colour Code: 2 Conductor, Black-White

Application: AUDIO, DATA, INSTRUMENTATION AND ELECTRONIC

Distributed by:

www.tacel.ca
info@tacel.ca



Head Office

179 Bartley Dr. Unit B
Toronto, ON M4A 1E6

Phone 416 750-4646
Toll Free 877 750-4646
Fax 416 750-4649