



SPECIFICATIONS

Body Material: High impact thermoplastic alloy blend
 Colors: Green, Black, Silver & Yellow
 To specify color add G for green, B for black, S for silver or Y for yellow in "X" position in part number.
 Melt Temperature: 500°F (260°C)
 High temperature dimensional stability.
 Chemical resistance to gasoline and oils.
 Weather resistant.
 UV stable.
 High impact strength at temperatures down to -40°F (-40°C).
 Bearing Material: Black Nylon
 Maximum Temperature: 170°F (77°C)
 Maximum Intermittent Temperature: 355°F (179°C)
 Low coefficient of friction.
 Chemical resistant.
 Good abrasion resistance.
 High strength.
 Button Material: 303 Stainless
 Actuating Force: 3 ±1 lbs.
 Actuating Stroke: .25"
 Switch:
 Piezo driven solid state switch.
 Operating Temperature: -40°F to 221°F (-40°C to 105°C)
 Operating Voltage: 8-36V AC or DC
 Max Current: .3A fused (auto resetting)
 Typical Life: Greater than 20 million operations.

Distributed by:



www.tacel.ca info@tacel.ca

Head Office

179 Bartley Dr. Unit B
 Toronto, ON M4A 1E6
 Phone 416 750-4646
 Toll Free 877 750-4646
 Fax 416 750-4649

INFORMATION ON THIS DOCUMENT IS PROPRIETARY TO POLARA AND SHALL NOT BE USED, COPIED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT OF POLARA.

10-0-05	C	22294	BB							
Revised - 10/20/05										
02-28-02	B	21827	BB	CLM	LB	WR	FB	RVC	JMc	
09-13-01	A	21776	BB	CLM	LB	WR	FB	RVC	JMc	
REV. DATE	LTR	E.C.O. NO.	BY	CKR	ENG	DSN	MFG	QA	FNL	

POLARA ENGINEERING INC.
 4115 W. ARTESIA AVE. FULLERTON, CA. 92833

TOLERANCES: .XXX ±.005 .XX ±.02 (EXCEPT AS NOTED) SCALE 1:2

DRAWN BY BB	CKR. CLM	ENG. MGR. LB	MFG. MGR. FB	SHEET 1 OF 1
DATE 08-05-99	DSN. ENG. WR	Q.A. APP. RVC	FINAL APP. JMc	USE

TITLE: MOVING PUSH BUTTON w/ SS CAP

DWG. NO. MPBS-X